



Programmatore Touch screen TCW 7" con USB e Wi-fi totalmente user-friendly grazie ad un display intuitivo e multifunzione.
Full color touch screen programmer TCW 7" with USB and Wi-fi, totally user-friendly with a multifunction intuitive display.

Garanzia fino a 3 anni.
Extended 3 years warranty



336.59T

Unita' di nastratura a colonna adatta per qualsiasi prodotto, dai capi estremamente elasticizzati, giacche waterproof, calzature (colonna posteriore intercambiabile). Grazie allo speciale sistema di riscaldamento con surriscaldatore in ottone e singola resistenza di 1500 Watt (con garanzia fino a 3 anni) i consumi elettrici ed aria compressa sono estremamente ridotti. L'unita' puo' essere configurata con taglio nastro o con riscaldamento guida calda. La 336.59T e' inoltre fornita con ruote motorizzate con effetto differenziale, dispositivo per controllo tensione nastri (902.01) che permette curve raggiate, Touch Screen a colori di ultima generazione per la programmazione e salvataggio dei parametri del ciclo di lavoro. La macchina e' inoltre predisposta su richiesta per l'installazione dei dispositivi di prelaminazione elastico (903.01)

336.59T

Seam sealing unit suitable for any kind of application as high stretch garments, waterproof jackets as well footwear (back interchangeable post). Thanks to the special designed heating system, made of brass and single heating element of 1500 Watt (warranty up to 3 years) the electrical and compressed air consumptions are drastically reduced. The unit can be configured with front cutter or heated guide. The 336.59T is also supplied with motorized rollers and differential control, electronic metering device for tape tension control (902.01), intuitive colour Touch Screen for parameters programming and data saving. Upon request the machine can be supplied with pre-lamination device (903.01) and electronic metering device (902.01)



Applicazioni
Applications



— Elastico/Tape
— Adesivo/Adhesive
— Tessuto/Fabric

Technical details

336.59T **Dimension:** (mm W x H x D) 1050 x 1400 x 600 | **Weight:** 145 Kg
Compressed air: pipe connection 1xø10 mm | **Pressure** 6 ATE | **Consumption** 26NL/min
Electric power: 1,8Kw | **Consumption** 1,35Kw/h

