

Chair-cover

379.88 **macpi**



379.88

Manichino elettropneumatico vaporizzante e soffiante per lo stiro di coprisedia asciutti e bagnati/centrifugati, completo di:

- regolazione pressione trazione fianchi;
- regolazione pressione chiusura pale;
- regolazione ventilazione con inverter;
- programmatore dotato di touch- screen con menu disponibile in varie lingue per il controllo di tutte le funzioni e dei parametri;
- predisposizione per allaccio centralizzato di vapore 6 Bar e aria compressa 6 Ate;
- soffiaggio con elettroventilatore incorporato da 2,25 Kw
- struttura intercambiabile adatta a ricevere le varie tipologie di coprisedia, completa di rivestimento;
- pale di bloccaggio laterali ad azionamento manuale, complete di rivestimento.



379.88

Electropneumatic steaming and blowing dummy for the pressing of dry and wet/centrifuged chair-cover Complete with:

- adjustable side tensioning pressure
- adjustable closure of the garment's blocking device
- adjustable ventilation with inverter
- programmer complete with touch screen with a menu available in different languages for all functions and parameters control
- foreseen to be connected to steam 6 Bar and compressed air 6 Ate main plant
- blowing through built-in electric fan 2,25 kw
- interchangeable frame adapted to receive different kind of chair-covers, complete with cover
- manual lateral blocking device, complete with cover.

Technical details

379.88

Dimension: (mm W x H x D) 1450 x 1670 x 1125 | **Weight:** 175 Kg
Compressed air: pipe connection 1x ø6 mm | **Pressure** 6 ATE | **Consumption** 3,14NL/min
Steam: pipe connection 1x ø3/8" GAS | **Exerted pressure** 6 ATE | **Consumption** 15/20 KG/h
Electric power: cable 5x2,5 | **Install power** 2,4Kw | **Consumption** 1,7Kw/h