




Rotazione veloce, ottenuta con l'applicazione di sistemi, pneumatici di spinta e oleodinamici di frenata.

Fast rotation thanks to the pneumatic pushing system and oleodynamic stopping



Programmatore Touch screen 3,8" removibile
3.8" removable touch screen programmer

506.9124

macpi®



506-9124

I caroselli Macpi 506.37 e 507.37, oltre ad un elevato standard di qualità, sono progettati per alte produzioni. La macchina è attrezzata con due forme aspiranti inferiori con rotazione di 180° ed una forma superiore riscaldata elettricamente. Programmazione digitale della temperatura e dei tempi di adesivazione. Pressione regolabile fino a 6 bar.




506-9124

The carousel series 506.37 and 507.37 are designed to grant a large production output. The units are fitted with two rotating vacuum bucks (rotation at 180 degree) and one electric heated head. Touch Screen control for parameters setting. Adjustable pressure up to 6 bar. Upon request, the shapes can be provided with flapper screen.

FORME - SHAPES

9124



 **607.07**
Vacuum pump available

Technical details

506	Dimension: (mm W x H x D) 1620 x 1720 x 1610 Weight: 700 Kg
	Compressed air: pipe connection 1xØ16 mm Pressure 6 ATE - consumption 100NL/min
	Electric power: 6,2Kw Consumption 4,7Kw/h
506.37-9124	Dimension: Forma rettangolare media/ Medium size flat bed shape (750 x 500 mm)

